

DESIGNED TO RUN

iFuge M24PR

(Refrigerated High Speed Micro Centrifuge)

iFuge M24PR

(Refrigerated High Speed
Micro Centrifuge)

Usually, a jack of all trades is master of none, but the iFuge M24PR Multipurpose Versatile Laboratory Centrifuge is definitely the master of all trades as it cater to all of your centrifugation requirements.

Designed from scratch using the best quality raw materials, iFuge M24PR effortlessly incorporates unmatched performance, convenience and fool-proof safety features to give you a much-needed peace of mind.

Featuring exceptional and top of the range features like user-programmable interface, automatic internal diagnosis, emergency lid release, iFuge M24PR is one centrifuge that will blow others out of the water with its sheer intuitiveness and versatility.




It begins where others end

Powerful and reliable enough to replace all your existing centrifuges, iFuge M24PR goes where no other product has gone by providing virtually unlimited versatility in terms of usage as well as performance.



High Performance
Brushless DC Motor For A
Maintenance-free Long Life



Temperature Ranges
from -20°C to 40°C




Adjustable Speed Range
From 500 To 15000 RPM
(RCF 223889)



Drainage tube for easy
clearance of water droplet
without removing rotor
for cleaning

Microprocessor
Control For Quick &
Easy Programming




Large Back Lit LCD
Display For Easy Reading
Of Multiple Parameters



Intuitive Interface
For Quick And
Convenient Setting



User Programmable
Feature - User Can
Save Upto 99 Programs
Of 4 Lines Each



With great power
comes great responsibility

iFuge M24PR's exemplary performance is complemented by its range of expansive safety features designed to protect you against the most unlikely scenarios. Enjoy a complete peace-of-mind that comes with buying quality products directly from the manufacturer.



Short Spin Feature For
Short Centrifugation
& Fast Pelleting



One Touch Toggling
Between RCF & RPM



Timer Setting From
30 Sec To 999 Mins With
Infinite Mode



Electronic Imbalance
Detection For
Maximum Safety



Lid Lock Safety -
Will Not Open While
Rotor Is Running



Emergency Lid Release
For Additional Safety




Less effort more work

Your convenience takes a priority with iFuge M24PR which is designed to deliver high performance at a fraction of the effort that you would require with other centrifuges. Now, experience what utter effortlessness feels like with the iFuge M24PR.



Designed To Operate At Low Noise Levels For Healthier Laboratory Environment



Low Height Design For Easy Loading And Unloading Of Sample

4 Rotor Options



ROTOR OPTIONS



8 x 5ml
(18461 g)



24 x 2ml
(21420 g)



44 x 2ml
(22388 g)



4PCR STRIP
(15397 g)

Specifications

Specifications	iFuge M24PR
Rotor Capacity	24 x 1.5 / 2 ml microtubes (Optional)
	44 x 1.5 / 2 ml microtubes (Optional)
	8 x 5 ml (Optional)
	4 PCR strips (Optional)
Temperature Range	-20°C to 40°C
Speed Setting	500 - 15000 RPM
Time Setting	30 secs to 999 mins & infinite mode
Display	Large back lit LCD display
Programmable Feature	User can set and save up to 99 user defined programs of lines each
Lid Lock Safety	Yes
Imbalance Detection	Yes
Dimension (W x D x H)	720 x 325 x 305 mm

Ordering information

iFuge M24PR		
Product Name	Cat #	Details
iFuge M24	M24-2111 EU/UK/AUS	M24 Metal Body - Refrigerated Centrifuge with EU/UK/AU Cable in 220V

Accessories		
Part Name	Cat #	Details
24 Slot Rotor	M24-R24	1.5/2 ml tube rotor with lid
24 Slot Rotor Lid	M24-R24E	Rotor lid for 24 slot rotor
44 Slot Rotor	M24-R44	1.5/2 ml tube rotor with lid
44 Slot Rotor Lid	M24-R44E	Rotor lid for 44 slot rotor
8 Slot Rotor	M24-R8X5	5 ml tube rotor with lid
8 Slot Rotor Lid	M24-R8X5E	5 ml tube rotor with lid
PCR Rotor	M24-R4X8	PCR strip rotor with lid
PCR Rotor Lid	M24-R4X8E	PCR strip rotor lid
Allen Key	M24-A	-
Power Cord	M24-C-EU/UK/AU/US	-

NEUATION
TECHNOLOGIES

www.neuation.com

AN ISO 9001 : 2015 & ISO 13485 : 2016 CERTIFIED MFG. COMPANY

*We also execute OEM projects. Specifications can be changed without notice for quality improvement.